



Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: The engine and emission control systems produced by the manufacturer are certified as described below for use in on-road motor vehicles with a manufacturer's GVWR over 14,000 pounds. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	ENGINE SIZES (L)	FUEL TYPE ¹	STANDARDS & TEST PROCEDURE	INTENDED SERVICE CLASS ²	ECS & SPECIAL FEATURES ³	IDLING EMISSIONS ⁵ CONTROL
2008	8VPTH16.1H01	16.1	Diesel	Diesel	HHDD	DDI, TC, CAC, ECM, EGR, PTOX	30g
ENGINE (L)	ENGINE MODELS / CODES (rated power, in hp)						
16.1	See attachment for engine models and ratings						

¹ =not applicable; GVWR=gross vehicle weight rating; 13 CCR xyz=Title 13, California Code of Regulations, Section xyz; 40 CFR 86.abc=Title 40, Code of Federal Regulations, Section 86.abc;
² liter; hp=horsepower; kw=kilowatt; hr=hour;
³ CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85=85% ethanol fuel; MF=multi fuel a.k.a. BF=bi fuel; DF=dual fuel; FF=flexible fuel;
⁴ L/M/H HDD=light/medium/heavy heavy-duty diesel; UB=urban bus; HDO=heavy duty Otto;
⁵ ECS=emission control system; TWC/O=C=three-way/oxidizing catalyst; NAC=NOx adsorption catalyst; SCR-U / SCR-N=selective catalytic reduction - urea / -- ammonia; WU (prefix) =warm-up catalyst; DPF=diesel particulate filter; PTOX=periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; HAFS/AFS=heated/air-fuel-ratio sensor (a.k.a., universal or linear oxygen sensor); TBI=throttle body fuel injection; SF/IMPI=sequential/multi port fuel injection; DGI=direct gasoline injection; GCARB=gaseous carburetor; IDI/DDI=indirect/direct diesel injection; TC/SC=turbo/super charger; CAC=charge air cooler; EGR / EGR-C=exhaust gas recirculation / cooled EGR; PAIR/AIR=pulsed/secondary air injection; SPL=smoke puff limiter; ECM/PCM=engine/powertrain control module; EM=engine modification; 2 (prefix)=parallel; (2) (suffix)=in series;
⁶ ESS=engine shutdown system (per 13 CCR 1956.8(a)(6)(A)(1); 30g=30 g/hr NOx (per 13 CCR 1956.8(a)(6)(C); ALT=alternative method (per 13 CCR 1956.8(a)(6)(D); Exempt=exempted per 13 CCR 1956.8(a)(6)(B) or for CNG/LNG fuel systems; N/A=not applicable (e.g., Otto engines and vehicles);
 (Rev.: 2007-12-20)

Following are: 1) the FTP exhaust emission standards, or family emission limit(s) as applicable, under 13 CCR 1956.8; 2) the EURO and NTE limits under the applicable California exhaust emission standards and test procedures for heavy-duty diesel engines and vehicles (Test Procedures); and 3) the corresponding certification levels, for this engine family. "Diesel" CO, EURO and NTE certification compliance may have been demonstrated by the manufacturer as provided under the applicable Test Procedures in lieu of testing. (For flexible- and dual-fueled engines, the CERT values in brackets [] are those when tested on conventional test fuel. For multi-fueled engines, the STD and CERT values for default operation permitted in 13 CCR 1956.8 are in parentheses.).

in g/bhp-hr	NMHC		NOx		NMHC+NOx		CO		PM		HCHO	
	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO	FTP	EURO
STD	0.14	0.14	*	*	*	*	15.5	15.5	0.01	0.01	*	*
FEL	*	*	1.16	1.16	1.3	1.3	*	*	*	*	*	*
CERT	0.04	0.03	1.02	1.04	1.1	1.1	*	*	0.002	0.000	*	*
NTE	0.21		1.74		2.0		19.4		0.02		*	

¹ g/bhp-hr=grams per brake horsepower-hour; FTP=Federal Test Procedure; EURO=Euro III European Steady-State Cycle, including RMCSET=ram mode cycle supplemental emissions testing; NTE=Not-to-Exceed; STD=standard or emission test cap; FEL=family emission limit; CERT=certification level; NMHC/HC=non-methane/hydrocarbon; NOx=oxides of nitrogen; CO=carbon monoxide; PM=particulate matter; HCHO=formaldehyde;

BE IT FURTHER RESOLVED: Certification to the FEL(s) listed above, as applicable, is subject to the following terms, limitations and conditions. The FEL(s) is the emission level declared by the manufacturer and serves in lieu of an emission standard for certification purposes in any averaging, banking, or trading (ABT) programs. It will be used for determining compliance of any engine in this family and compliance with such ABT programs.

BE IT FURTHER RESOLVED: Except in vehicle applications exempted per 13 CCR 1956.8(a)(6)(B), engines in this engine family certified under 13 CCR 1956.8(a)(6)(C) [30 g/hr NOx] and section 35.B.4 of the incorporated "California Exhaust Emissions Standards and Test Procedures for 2004 and Subsequent Model Heavy-Duty Diesel Engines and Vehicles" (HDDE Test Procedures) adopted Dec. 12, 2002, as last amended Sep. 1, 2006, shall be provided with an approved "Certified Clean Idle" label that shall be affixed to the vehicle into which the engine is installed.

BE IT FURTHER RESOLVED: The listed engine models have been certified to the split engine family standards under 13 CCR 1956.8(b) [diesel engines] or 13 CCR 1956.8(d) [Otto engines] and the incorporated 40 CFR 86.007-15(m)(9).

BE IT FURTHER RESOLVED: For the listed engine models the manufacturer has submitted the materials to demonstrate certification compliance with 13 CCR 1965 (emission control labels) and 13 CCR 2035 et seq. (emission control warranty).

BE IT FURTHER RESOLVED: The listed engine models are conditionally certified pending final approval of "Certified Clean Idle" vehicle label. The manufacturer has until March 31, 2008 to resolve concerns on this conditional certification. This Executive Order is effective through March 31, 2008; engines produced after this date are not covered by this Executive Order.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 15 day of February 2008.

Annette Hebert, Chief
Mobile Source Operations Division

Engine Model Summary Form

Manufacturer: Volvo Powertrain North America, a Division
 Engine category: On-highway HDDE
 EPA Engine Family: 8VPTH16.1H01
 Mfr Family Name: 8VPTH16.1H01
 Process Code: New Submission

1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate: mm/stroke@peak torque	8.Fuel Rate: (lbs/hr)@peak torque	9.Emission Control Device Per SAE J1930
N/A	D16F - 600	524 @ 2000	299.8	198.0	2091 @ 1200	400.0	158.5	EM,EC,TC,CAC, DI,EGR,DPF
N/A	D16F - 550	524 @ 2000	299.8	198.0	1887 @ 1100	370.3	134.5	"
N/A	D16F - 535	510 @ 2000	284.7	188.0	1887 @ 1100	370.3	134.5	"
N/A	D16F - 500	466 @ 2000	261.2	172.5	1887 @ 1100	370.3	134.5	"
N/A	D16F - 500	466 @ 2000	261.2	172.5	1887 @ 1100	370.3	134.5	"
N/A	D16F - 500	466 @ 2000	261.2	172.5	1785 @ 1100	351.0	127.5	"
N/A	D16F - 500	466 @ 2000	261.2	172.5	1683 @ 1100	329.0	119.5	"
N/A	D16F - 450	408 @ 2000	233.2	154.0	1785 @ 1100	351.0	127.5	"
N/A	D16F - 450	408 @ 2000	233.2	154.0	1785 @ 1100	351.0	127.5	"
N/A	D16F - 450	408 @ 2000	233.2	154.0	1683 @ 1100	329.0	119.5	"
N/A	MP10 - 605C	524 @ 2000	299.8	198.0	2091 @ 1200	400.0	158.5	"
N/A	MP10 - 565C	524 @ 2000	299.8	198.0	1887 @ 1100	370.3	134.5	"
N/A	MP10 - 515C	466 @ 2000	261.2	172.5	1887 @ 1100	370.3	134.5	"

ATTACHMENT

A-242-0049